



CapSwitcher®

Capacitor
Switching Device
15 kV – 38 kV

Provided by Northeast Power Systems, Inc.
www.nepsi.com

Purpose specific device provides reliable, long-life performance.

The need for quality power has never been greater. This has led to an increase in the use of capacitor banks to improve power factor. The Southern States **CapSwitcher**® high voltage capacitor switching device has been specifically developed to provide restrike free switching of capacitor banks. This reliable, long-life, special purpose SF₆ capacitor switch utilizes closing resistors for mitigating voltage transients and current inrush.

FEATURES

- Closing resistors minimize voltage and current transients
- Design virtually eliminates restrikes
- Simple, cost effective, mechanical design that provides repeatability
- Long Life (10,000 operations)
- Eliminates need for inrush reactors

SPECIFICATIONS

Maximum Voltage Ratings

15.5 kV – 38 kV

Capacitive Current Switch Rating

600 A

Short Time Withstand Ratings

40 kA RMS Sym (2 sec)

Peak capacitive Inrush Current

23 kA @ 5400 Hz

Application

- Single Bank or Back-to-Back
- Grounded or Ungrounded

CapSwitcher®

Capacitor
Switching Device
15 kV – 38 kV



RATINGS

Maximum Voltage Rating (kV)	15.5	27	38
BIL (kV)	110	150	200
Rated Power Frequency	50/60 Hz		
Continuous Current	600 A		
Capacitive Switching Current	600 A		
Short-Time Symmetrical Withstand	40 kA RMS		
Rated High-Frequency Transient-Making Current	42 kA peak at 8100 Hz		
Endurance Life	10,000 operations		
Ambient Temperature Rating	-50° C to +50° C standard		

Capacitor Switching Ratings (IEEE C37.09a-2005)

Maximum Voltage Rating (kV)	15.5	27	38
Capacitive Switching Current	600 A		
High Frequency Transient Making Current	23 kA peak at 5400 Hz		
Closing Resistor Value	6 Ω, 10 Ω, or 20 Ω	12 Ω, 20 Ω, or 30 Ω	12 Ω, 30 Ω, or 90 Ω

KEY ADVANTAGES

- Makes and breaks circuit in SF₆
- Designed and tested for restrike-free performance
- Closing resistors provide reliable and consistently repeatable transient suppression
- Multiple resistor sizes allow performance optimization
- Closing resistor eliminates need for inrush reactors
- Pressure gauge on each interrupter provides local visual gas system status
- Designed to mount on new or existing capacitor bank racks
- Straight forward mechanical design insures long life, repeatable operation
- Ships assembled and pressurized minimizing installation and setup

Rated Duty Cycle:

- Standard (Slow Close): 8 sec – C – 6 cycle – O
- Fast Close (includes Close Coil): C – 6 cycle – O – 8 sec



The Quality Name in High Voltage Switching

30 Georgia Avenue Hampton, GA 30228
P 770-946-4562 F 770-946-8106
sales@southernstatesLLC.com
www.southernstatesLLC.com

Publication No. CF809-CAP 38-R1 08032010
Printed in USA August 2010 ©2010 Southern States, LLC